

Pomelli a stella· DIN 6336 in plastica EH 24670.

Descrizione prodotto



Materiale


Bussola

- Ottone
- Acciaio, zincato
- Acciaio inox A2

Impugnatura

- DIN 7708 - Plastica (PF 31), nero RAL 9005

Disegno



Caratteristiche

Dimensioni						max. [°C]	[g]	Cod.
d ₁	d ₅	d ₇	h ₃	h ₄	t ₃			
Con bussola filettata, forma K, Ottone								
20	M 4	10	7	13	6,5	110	3,4	24670.0220
Con bussola filettata, forma K, Acciaio								
25	M 5	12	8	16	9,5	110	7,4	24670.0225
32	M 6	14	10	20	12,0	110	11,0	24670.0232
40	M 8	18	13	25	14,0	110	22,0	24670.0240
50	M10	22	17	32	18,0	110	40,0	24670.0250
63	M12	26	21	40	22,0	110	83,0	24670.0263
80	M16	35	25	50	30,0	110	161,0	24670.0280
Con bussola filettata, forma K, Acciaio inox								
25	M 5	12	8	16	9,5	110	7,4	24670.1225
32	M 6	14	10	20	12,0	110	11,0	24670.1232
40	M 8	18	13	25	14,0	110	22,0	24670.1240
50	M10	22	17	32	18,0	110	40,0	24670.1250
63	M12	26	21	40	22,0	110	83,0	24670.1263
80	M16	35	25	50	30,0	110	161,0	24670.1280

Esempio di applicazione

